

can-am

OUTLANDER X mr 1000R

2021

HIGHLIGHTS

- Rotax® V-Twin engine
- Arched double A-arm front suspension with front sway bar
- Torsional Trailing-Arm Independent (TTI) rear suspension
- Front and rear FOX¹ 1.5 PODIUM¹ shocks
- Intelligent Throttle Control (ITC™) with riding modes
- 30 in. ITP¹ Cryptid¹ tires
- 14 in. cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok¹ QE auto-locking front differential
- Relocated radiator
- 3,500 lb (1,588 kg) winch
- Heavy-duty front and rear bumpers
- Mud-riding footrests
- 59 in. wheelbase
- Multifunction digital gauge
- X-package coloration, graphics and seat cover
- Mudguards

SPECIFIC TO VISCO-4LOK PACKAGE

- NEW Visco-4Lok with rider lockable front differential
- Full wrap handguards

ENGINE	1000R	1000R with Visco-4Lok
Type	91 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled with relocated radiator	
Fuel Delivery System	Intelligent Throttle Control (ITC) with Electronic Fuel Injection (EFI)	
Transmission	CVT, P/R/N/H/extra-low L, standard engine braking	
Drive Train	Selectable 2WD/4WD with Visco-Lok QE auto-locking front differential	Selectable 2WD/4WD/Lock 4WD with Visco-4Lok rider lockable front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar
Front Shocks	FOX 1.5 PODIUM
Rear Suspension	Torsional Trailing-Arm Independent (TTI)
Rear Shocks	FOX 1.5 PODIUM

TIRES & WHEELS

Front Tires	ITP Cryptid ¹ 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid ¹ 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Wheels	14 in. cast aluminum

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper



- Granite Gray, Black & Manta Green / 1000R
- Neo Yellow & Black / 1000R (with Visco-4Lok)

DIMENSIONS & CAPACITIES	1000R	1000R with Visco-4Lok
Estimated Dry Weight*	1,014 lb (460 kg)	
L x W x H	97 x 50 x 51.5 in. (246 x 127 x 131 cm)	
Wheelbase	59 in. (149.9 cm)	
Ground Clearance	13 in. (33 cm)	
Seat Height	36.75 in. (93.3 cm)	
Rack Capacity	Rear: 200 lb (90 kg)	
Storage Capacity	Rear: 5.7 gal (21.4 L)	
Towing Capacity	1,650 lb (750 kg)	
Fuel Capacity	5.4 gal (20.5 L)	

FEATURES

Gauge	7.6 in. wide digital display: Speedometer, tachometer, odometer, trips and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge, clock	
Instrumentation	Lighter-type DC outlet in console, standard connector in the back (15 A)	
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)	
Lighting	230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light	
Winch	3,500 lb (1,588 kg) winch	
Seat	Standard	
Protection	Heavy-duty front and rear bumpers Mud-riding footrests Mudguards	Heavy-duty front & rear bumpers Full wrap handguards Mud-riding footrests Mudguards

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months

© 2020 Bombardier Recreational Products Inc (BRP). All rights reserved. ®, TM and the BRP logo are registered trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. ‡Top Speed limited to a maximum of 100 km/h (62 mph). For other jurisdictions, see your local dealer. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at any time to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV driver take a training course. For safety and training information, see your dealer or, in the U.S.A. call the ATVSafetyInstitute at 1-800-887-2887. In Canada, call the Canadian Safety Council at 1-613-739-1535, ext. 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding, alcohol and drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90 cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

